

COBRA[®] PLUS

Unmatched Flexibility | Extremely Efficient | Superior Functionality



HALOILA
Machines & Service

www.haloila.com

Semi-automatic stretch wrapping machine

COBRA[®] PLUS

Flexible, efficient and functional pallet wrapping solution

Unmatched Flexibility

Thanks to the rotating arm technology, the pallet load does not move during the stretch wrapping process. Therefore, the Cobra Plus is ideal for wrapping loads that are unstable, light, very heavy or odd-shaped – whatever the product type. The Cobra Plus comes standard with an independent floor stand, but can also be mounted to a column or wall. This innovative design also comes standard with an adjustable wrapping arm that can easily be modified to accommodate larger loads at no additional cost and provides the versatility to adapt to future needs.

Extremely Efficient

The motorized power pre-stretch system with adjustable film tension control guarantees optimal film usage. Also, by providing variable film tension control throughout the wrap cycle, superior load containment can be achieved while eliminating film breaks and product damage. The patented film carriage ensures consistent performance and optimal film consumption.

Superior Functionality

Four individual wrap programs can be stored using the touch screen HMI for simple operation of the machine. The programs include eight functions which can be adjusted to meet the demands of the most challenging applications.



The rotating arm can be easily adjusted to achieve a wrapping diagonal of 1800 mm or 2200 mm ; offering extreme versatility at no additional cost.



The power pre-stretch carriage offers optimal load containment and optimal film usage. It also allows for easy film threading.



Easy to use for simple operation and maximum functionality. Adjustments for the number of wraps, wrap pattern, film tension, overlap, overwrap, and up/down speed are standard.

Dimensions	Technical Details	Options
Overall Height	Rotation Speed	Height Extension Upgrades
3100 mm (standard)	Up to 12 RPM	Column/ Wall Mounting Kit
3450 mm or 3800 mm (optional)	Capacity	Mechanical Roping Device
Max. Pallet Height	Up to 35 pallets/hr	
2200 mm (standard)	Weight	
2550 mm or 2900 mm (optional)	640 kg	
Maximum Pallet Diagonal	Voltage	
1800 mm or 2200 mm	230 V - 1 phase - 50 Hz	
	Control	
	PLC and touchscreen HMI	
	Film Width	
	500 mm	
	Max. film dia.	
	250 mm	
	Standard Mounting	
	Floor Stand	

HALOILA

Machines & Service

Haloila, FI-21250 Masku (Finland), Tel.: (+358) 2 437 6111, Fax: (+358) 2 437 6211
 octopus.gb@team.haloila.com octopus.global@team.haloila.com www.haloila.com